



## **DECORATIVE WATER-BASED EXTERIOR PRODUCT GROUP**

# **Tempo Siliconed Exterior Primer**

### **PRODUCT DESCRIPTION**

Silicone acrylic emulsion-based, pigmented, top coat exterior primer with high adherence.

### **FEATURES**

Forms a binding bridge between the paint and the surface with high adherence. Reduces paint consumption. Enables moisture on the surface to be discharged thanks to its breathability. Prevents possible application errors by allowing the top coat to be absorbed by the surface at different rates.

### **APPLICATION SURFACES**

Used as a primer on smooth and rough plasters, mineral-based surfaces, exposed concrete and faded self-supporting silicone or acrylic-based previously painted surfaces.

### **APPLICATION**

Ensure that the application surface is solid, clean, dry, self-supporting, and free of any loose layers/dirt/grease. Wait for defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days). Apply Tempo Silicone Exterior Primer in a single coat using a brush, roller or spray gun. Ensure that the surface and ambient temperatures are between +5 °C and +30 °C. Do not apply at windy environments and under direct sunlight. Start the paint application 6-8 hours after priming. Used tools should be cleaned with water after application. Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

### **Airless Spraying:**

Pressure: 140 bar

Nozzle Angle: 50°

Nozzle Size (inch): 0.013"

Thinning: 5%

### **THINNING RATIO**

Thin by 10% maximum with clean water in brush and roller applications. Thin by 5% maximum with clean water in spraying.

### **DRYING TIME (at 20 °C, 65% RH):**

Primer drying: 6-8 hours

### **BETEK BOYA VE KİMYA SAN. A.Ş.**

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

[www.tempoboya.com.tr](http://www.tempoboya.com.tr)



## CONSUMPTION

9 m<sup>2</sup> area can be primed in a single coat with 1 kg. It can be change due to surface kind, thinning ratio , weather conditions and painter. Perform a controlled sample run to estimate the precise consumption.

## STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

## PACKAGING

20 kg, 3.5 kg

## WARNING WORD

Caution

## HAZARD PHRASE

H317 May cause an allergic skin reaction.

## PRECAUTIONARY PHRASES

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

## Pose No.

15.540.1304, 15.540.1305, 15.540.1309

## Rate No.

10.300.1172

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 45001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.**

**Rev30 May 2022**

## BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr