



DECORATIVE WATER-BASED EXTERIOR PRODUCT GROUP

Tempo Exposed Concrete Primer

PRODUCT DESCRIPTION

Polymer modified resin-based interior and exterior primer which is used to improve surface adherence before plaster and cement-based mortar applications on exposed concrete.

FEATURES

Used to improve adherence on surfaces like exposed concrete walls, columns, and ceilings. Improves the performance of top coat product. Used to improve surface adherence before applying plaster and cement based mortar on exposed concrete.

APPLICATION SURFACES

Apply to exposed concrete surfaces after application of plaster and cement-based mortar.

APPLICATION

Ensure that the application surface is solid, dry, clean, and self-supporting. Remove any mold grease, dirt, dust and loose layers. Wait for defined setting periods on concrete, exposed concrete and new plastered surfaces (28 days). Ensure that the ambient and the surface temperatures are between +5 °C and +30 °C during application and until the end of drying time, and protect the surface from all kinds of precipitation, dew and frost. Recommended to be applied in a way without being exposed to direct sunlight in hot weather. Add maximum 40-50% water based on desired consistency, mix with a low speed mixer, and apply Tempo Exposed Concrete Primer on the surface with sheepskin roller in a single coat. Mix Tempo Exposed Concrete Primer regularly during application. Wait until the surface is fully dry for plaster and mortar application (approximately 24 hours). Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

THINNING RATIO

Recommended to be applied in a single coat after thinning by 35-40% with clean water in roller applications.

DRYING TIME (at 20 °C, 65% RH):

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperatures).

CONSUMPTION

5 m² area can be primed in a single coat with 1 kg. It can be change due to surface kind, thinning ratio , weather conditions and painter. Perform a controlled sample run to estimate the precise consumption..

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight.

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr



PACKAGING

12 kg

WARNING WORD

Caution

HAZARD PHRASE

H317 May cause an allergic skin reaction.

PRECAUTIONARY PHRASES

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.



Complies with TS 13744.

Pose No.

15.540.1201

Rate No.

10.300.1173

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 45001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev30 May 2021

BETEK BOYA VE KİMYA SAN. A.Ş.

Gebze Organize Sanayi Bölgesi Tembelova Alanı 3200. Sokak No: 3206 Gebze / KOCAELİ - TURKEY

Phone: +90 (0216) 571 11 90 (pbx)

www.tempoboya.com.tr