

Preparation date: 26.12.2019 Revision: 26.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Synthetic paint
- 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A.S.

G.O.S.B. Tembelova Alani 3200 Sokak No:3206

41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

Fax: 00 90 262 641 21 68 murat.kucukkul@betek.com.tr

• Further information obtainable from: R&D Department • 1.4 Emergency telephone number: 0090 262 678 30 00

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling: Distillates (petroleum), hydrotreated light Solvent naphtha (petroleum), medium aliph. naptha(petroleum), hydrotreated heavy toluene

(Contd. on page 2)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains 2-butanone oxime. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

· Dangerous compon	ents:	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	10-25%
EINECS: 265-149-8	🚸 Flam. Liq. 3, H226; \delta Asp. Tox. 1, H304	
CAS: 64742-48-9	naptha(petroleum), hydrotreated heavy	2.5-10%
EINECS: 265-150-3	♦ Asp. Tox. 1, H304	
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	2.5-10%
EINECS: 265-191-7	 ♦ Flam. Liq. 3, H226; ♦ STOT RE 1, H372; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332 	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%
EINECS: 265-199-0	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Acute Tox. 4, H332; STOT SE 3, H335	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.

(Contd. on page 3)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

General protective and hygienic measures:

 ${\it Keep \ away \ from \ foodstuffs, \ beverages \ and \ feed.}$

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Initial boiling point and boiling range: Undetermined.

· Flash point:	Undetermined
· Flammability (solid, gas):	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 5)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 4)

	(Conta. of page
Density at 20 °C:	1.21 g/cm^3
· Solubility in / Miscibility with	
water:	Fully miscible.
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
64742-88-7 Solvent naphtha (petroleum), medium aliph.				
Oral	LD50	>6500 mg/kg (rat)		
Dermal	LD50	>3000 mg/kg (rab)		
Inhalative	LC50/4 h	>14 mg/l (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 5)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN1993
1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE TURPENTINE SUBSTITUTE), special provision 640E
FLAMMABLE LIQUID, N.O.S. (TOLUENE, TURPENTIN SUBSTITUTE)
3 (F1) Flammable liquids. 3
3 Flammable liquids.
3

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Ann	· ·
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	<i>5</i>
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1993, FLAMMABLE LIQUID, N.O.S. (TOLUEN
_	TURPENTINE SUBSTITUTE), special provision 640E, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 8)

Preparation date: 26.12.2019 Revision: 26.12.2019

Trade name: TEMPO LÜKS SENTETIK BOYA TEMPO SYNTHETIC PAINT

(Contd. of page 7)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

GB